

Siliconized Acrylic Sealant

Siliconized acrylic sealant is a single-component, acrylic dispersion based sealant which is reinforced with silicone emulsion

Properties

- One-component.
- Very easy application.
- Form permanently water repellent layer after curing.
- Resistant to weather conditions.
- Remains flexible for a long time after curing.
- Paintable.
- Does not effect the application surface.
- Elastic. It has bright, glossy appearance.
- It can be used for all porous surfaces such as brick, concrete and wood.
- Water, wind and moisture resistant on aluminum, wood and PVC frames and windows.

Packaging

310 ml x 25 per box

Colors

White, Grey

Application Details

Expanding fuga between prefabricate construction element. Assembly wood, PVC, iron and aluminium joinery. Joints in stone, wood, concrete, plaster and brick works etc. Sealing of window and door frame to masonry.

Shelf Life

The shelf life is 12 months at temperatures between +5°C and +25°C.



TMPU001

Pu Foam

PU Foam is polyurethane based, moisture cured, one component filling and insulation material

Properties

- One-component.
- Moisture cured.
- Excellent adhesion to most construction materials such as wood, concrete, tile, metal and aluminum (except polyethylene, silicone and teflon).
- Thermal and acoustic insulation.
- Cuttable and paintable after curing.
- Very good expansion capacity.

Packaging

750 ml - 845 g x 16 per box

Colors

Foam Color: Yellow

Application Details

Assembling and sealing of windows and door frames, filling of cavities, sealing of openings in all roof constructions, thermal and acoustic insulation.

Shelf Life

The shelf life is 12 months at temperatures between +5°C and +25°C.



TMPU004

Pu Sealant

Single-component, moisture curing, polyurethane-based sealant material.

Properties

- One-component.
- Easy application with gun.
- Thixotropic.
- Cures with the humidity in the air.
- Paintable.
- No volume change.
- Resistant to weather conditions and water.
- Permanent elasticity.

Packaging

280 ml aluminum cartridge x 25 per box 600 ml aluminum sausage x 20 per box

Colors

White, Grey, Black

Application Details

Is capable of adhesion to cement-based building materials, brick, ceramic, marble, glass, wood, galvanized steel, aluminum and most plastic surfaces. Used in construction industry, in the cavities of the joints between building elements Used for joints and assembly of aluminum, PVC, wooden framing Used for laying of roof tiles.

Shelf Life

The shelf life is 9 months at temperatures between +5°C and +25°C.



TMPU003 **TMPU002**